

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 February 2004 (26.02.2004)

PCT

(10) International Publication Number
WO 2004/017685 A1

(51) International Patent Classification⁷: **H05H 15/00**,
G21G 1/10

(21) International Application Number:
PCT/UA2003/000015

(22) International Filing Date: 19 May 2003 (19.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002086722 14 August 2002 (14.08.2002) UA

(71) Applicant (for all designated States except US): **LTD
COMPANY "PROTON-21"** [UA/UA]; 48-A Chernovola
Str., Vishnevoye, Kiev-Svyatoshinsky, Kievskaya obl.
08132 (UA).

(71) Applicant and

(72) Inventor: **ADAMENKO, Stanislav Vasilyevich**
[UA/UA]; Vasilenko ul., 19-39, Kiev, 03124 (UA).

(74) Agent: **KUTSEVICH, Valerii Lyudvikovich**; ul. Pol-
yamaya, 13-81, Kiev, 04201 (UA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,
MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ,
TM, TR, TT, TZ, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(48) Date of publication of this corrected version:


6 May 2004

(15) Information about Correction:

see PCT Gazette No. 19/2004 of 6 May 2004, Section II

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR COMPRESSING A SUBSTANCE BY IMPACT AND PLASMA CATHODE
THERETO



(57) Abstract: A method of compressing a substance by impact in axisymmetric relativistic vacuum diodes (RVD) having a plasma cathode and an anode-enhancer including: producing an axisymmetric target of a condensed substance, which functions at least as a part of the anode-enhancer; axially placing said electrodes; and pulse discharge of a power source via the RVD. To compress a substantial portion of the target substance to a superdense state, a plasma cathode is used in the form of a current-conducting rod comprising a dielectric end element having the perimeter of the rear end embracing the perimeter of the rod in the plane perpendicular to the axis of symmetry with a continuous gap, and the area of the emitting surface being greater than the maximum cross-section area of the anode-enhancer; the anode-enhancer is placed towards the plasma cathode so that the center of curvature of the working surface of the anode enhancer is located inside the focal space of the collectively self focussing electron beam; and the anode-enhancer is acted upon by an electron beam with an electron energy not smaller than 0.2 MeV, current density not smaller than 106 A/cm2 and duration not greater than 100 ns.

WO 2004/017685 A1